

BRICK VENEER c/w 1"  
(25mm) AIR SPACE  
AND BRICK TIES

FORM PANELS c/w INSERT  
WEBS-CUT TO SUIT FLOOR  
CONNECTION-  
ADDITIONAL FORM SUPPORT  
AS REQUIRED

WET SET DOWELS FIELD  
BENT INTO SLAB AS  
SPECIFIED

U BRACKET ANCHOR  
INSERT

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POUR OR AS  
SPECIFIED

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

NUDURA 8" (203mm)  
STANDARD FORM  
UNIT

GYPSUM BOARD  
FINISHED/FIRE STOP  
INSTALLED AT JOISTS  
AS PER CODE

COMPOSITE STEEL  
DECK-SLAB AND  
REINFORCEMENT AS  
SPECIFIED

OWSJ

INTERIOR INSULATION  
REMOVED AT JOIST  
LOCATIONS

1/2" (13mm) GYPSUM  
BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

**INTEGRATED BUILDING TECHNOLOGY**

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
COMPOSITE STEEL DECK-SLAB  
STEEL JOIST ON EXT. BEARING WALL  
INTERMEDIATE FLOOR CONNECTION  
BRICK VENEER FINISH

REV. NO.  
003 KS  
REV. DATE:  
MAR 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
D8C08  
SCALE:  
1 : 8